

Date: Wednesday, 11/21/2007 12:51:38 PM  
 User: Kim Johnston

## Process Sheet

Customer : CU-DAR001 Dart Helicopters Services	Drawing Name : LABEL
Job Number : 35944	
Estimate Number : 10124	
P.O. Number : <u>N/A</u>	Part Number : D2258200
This Issue : 11/21/2007 S.O. No. : <u>N/A</u>	Drawing Number : D2258 REV B1
Prsht Rev. : NC	Project Number : N/A
First Issue : <u>N/A</u> Type : PURCHASED PARTS	Drawing Revision : B1
Previous Run : 34588	Material : <u>N/A</u>
Written By : <u>[Signature]</u>	Due Date : 11/28/2007 Qty: 20 Um: Each
Checked & Approved By : <u>[Signature]</u>	
Comment : Est: B 04.04.15 Reformat; Clarify Step 2 KJ/RF	

## Additional Product

Job Number:



Seq. #:	Machine Or Operation:	Description :
---------	-----------------------	---------------

1.0	PG	PURCHASING
-----	----	------------



Comment: PURCHASING

Issue P/O: 5110C 10/11/22 (20)

Make D2258-200 read 200lb / 91kg as per Dwg D2258

Material: Red letters (1.00" min height) with adhesive back Manufacture from 3M 7mil masking film #8522CP or Avery IPM #2031

Material release note is required

2.0	D2258200P	Weight Placard 200lb
-----	-----------	----------------------



Comment: Qty.: 1.0000 Each(s)/Unit Total : 20.0000 Each(s)  
 WEIGHT PLACARD 200 LB

3.0	PACKAGING 1	PACKAGING RESOURCE #1
-----	-------------	-----------------------



Comment: PACKAGING RESOURCE #1

Receive and Inspect for transit damage

Ensure material release note is attached

C 7/14/27 (20)

4.0	QC6	DIMENSIONAL CHECK
-----	-----	-------------------



Comment: DIMENSIONAL CHECK

C 02/11/28 (20) Coates

5.0	PACKAGING 1	PACKAGING RESOURCE #1
-----	-------------	-----------------------



Comment: PACKAGING RESOURCE #1

Identify and Stock

Location: 5T23C 04/11/28 (20)

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: \_\_\_\_\_ PAR #: \_\_\_\_\_ Fault Category: \_\_\_\_\_ NCR: Yes ☒ No ☐ DQA: D Date: 9/11/08  
 QA: N/C Closed: \_\_\_\_\_ Date: \_\_\_\_\_

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Wednesday, 11/21/2007 12:51:38 PM  
User: Kim Johnston

## Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: LABEL

Job Number: 35944

Part Number: D2258200

Job Number:



Seq. #:

Machine Or Operation:

Description :

6.0

QC21

FINAL INSPECTION/W/O RELEASE



(20)

Comment: FINAL INSPECTION/W/O RELEASE

20 8/11/08

Job Completion



U 8.11.29

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: \_\_\_\_\_ PAR #: \_\_\_\_\_ Fault Category: \_\_\_\_\_ NCR: Yes No DQA: \_\_\_\_\_ Date: \_\_\_\_\_

QA: N/C Closed: \_\_\_\_\_ Date: \_\_\_\_\_

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

**NOTE:** Date & initial all entries




DESIGN B WILLIAMS	DRAWN BY K HAND	DART AEROSPACE LTD VICTORIA INTERNATIONAL AIRPORT, CANADA	
CHECKED <i>BW</i>	APPROVED <i>KA</i>	DRAWING NO. D2258	REV. B SHEET 1 OF 1
DATE 95.11.29		TITLE UTILITY BASKET PLACKARD	SCALE 1:1
A	94.07.28	NEW ISSUE	
B	95.11.29	ADDED NOTE	
BI	<del>4</del> RF 03.08.18	ADDED D2258-160	

RELEASED  
99.10.12 KE

1" RED LETTERS ADHESIVE BACK

MAXIMUM DISTRIBUTED LOAD  
XXX lb/ XXX kg

EXAMPLE

<u>PART #</u>	<u>LOAD</u>
D2258-132	132 lb/60 kg
D2258-200	200 lb/91 kg
D2258-220	220 lb/100 kg
 D2258-160	160 lb/73 kg

SHOP COPY  
RETURN TO  
ENGINEERING  
UNCONTROLLED COPY  
SUBJECT TO AMENDMENT  
WITHOUT NOTICE  
WORK ORDER  
NO. 35944



## PRODUCT DATA BULLETIN

Product Data Bulletin: A5-O

**Avery Graphics™ A5 Opaque**  
5-year **INTERMEDIATE** calendered vinyl film

Dated: 10/3/02

### Description:

Avery Graphics™ A5 Opaque intermediate films are flexible, high-gloss calendered vinyls designed for use on computer sign cutting equipment. This construction provides excellent cutting, weeding and transferring characteristics for signage applications.

Application information can be found in the Avery Graphics Application Guide.

For surface preparation, converting and printing, and application and removal instructions, please refer to the Avery Graphics Instructional Bulletin.

### Construction:

- Face Film: 3.2 mils opaque medium gloss intermediate calendered vinyl film
- Adhesive: 1.0 mil clear acrylic permanent solvent pressure-sensitive adhesive
- Liner: 78# bleached white kraft

### Physical Properties:

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

- Outdoor durability: 5 years when properly processed and applied (vertical exposure, unprinted film)\*\*
- Application surface contours: Flat and simple curves
- Minimum surface and air application temperature: +50° F (10° C)
- Service Temperature Range: -40° F to +180° F (-40° C to 82° C) (Reasonable range of temperatures which would be expected under normal environmental time and temperature conditions)
- Typical Chemical Resistance: Resistant to most mild acids, alkalis and salt solutions. See instructional bulletin for recommendations on cleaning.
- Shelf Life: One year when stored at the following temperatures and humidity conditions: 68° - 77° F (20° - 25° C) and 50±5% R. H.
- Typical Adhesion Values: **180° Peels**

Substrate	24 hrs	1 week
Stainless Steel	4.4 lbs/in	5.1 lbs/in
Glass	4.7 lbs/in	5.3 lbs/in

NOTE: Tested per ASTM D 1000. Always pre-test your specific substrate prior to actual application.

- Reflectivity: NA
- Typical Gloss\*: 70 at 60°



210 MAIN W.,  
HAWKESBURY, ONT. K6A 2H6  
Tel.: 613 632-5449  
Fax: 613 632-9491  
www.studiolettrage.on.ca

# INVOICE / FACTURE

VENDU À:  
SOLD TO:

LIVRÉ À:  
SHIPPED TO:

No.: 9538  
DATE: 11/26/2007  
PAGE 1 of 1  
Re: Quote No. 4275

Dart Aerospace Ltd  
1270 Aberdeen  
Hawkesbury, Ontario K6A 1K7

Dart Aerospace Ltd  
Hawkesbury, Ontario

ITEM ARTICLE	QTY QYÉ	UNIT UNITÉ	DESCRIPTION	GST TPS	PST TVP	UNIT PRICE PRIX UNITÉ	AMOUNT MONTANT
	20 110 1		D2258200p maximum 200lb d36711 red arrow on white printing set up	G G E		7.0000 0.4545 50.0000	140.00 50.00 50.00
			Subtotal:				240.00
			E - GST @ 6% G - GST @ 6%; PST @ 8% GST				14.40
			PST Exempt: #6122-5207				
			GST/TPS: R122278690				
po5110						<b>TOTAL</b>	254.40

Sold By:

*Merci! Thank You!*



## PRODUCT DATA BULLETIN

Product Data Bulletin: A5-O

### Avery Graphics™ A5 Opaque

5-year **INTERMEDIATE** calendered vinyl film

Dated: 10/3/02

#### Description:

Avery Graphics™ A5 Opaque intermediate films are flexible, high-gloss calendered vinyls designed for use on computer sign cutting equipment. This construction provides excellent cutting, weeding and transferring characteristics for signage applications.

Application information can be found in the Avery Graphics Application Guide.

For surface preparation, converting and printing, and application and removal instructions, please refer to the Avery Graphics Instructional Bulletin.

#### Construction:

- Face Film: 3.2 mils opaque medium gloss intermediate calendered vinyl film
- Adhesive: 1.0 mil clear acrylic permanent solvent pressure-sensitive adhesive
- Liner: 78# bleached white kraft

#### Physical Properties:

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

- Outdoor durability: 5 years when properly processed and applied (vertical exposure, unprinted film)\*\*
- Application surface contours: Flat and simple curves
- Minimum surface and air application temperature: +50° F (10° C)
- Service Temperature Range: -40° F to +180° F (-40° C to 82° C) (Reasonable range of temperatures which would be expected under normal environmental time and temperature conditions)
- Typical Chemical Resistance: Resistant to most mild acids, alkalis and salt solutions. See instructional bulletin for recommendations on cleaning.
- Shelf Life: One year when stored at the following temperatures and humidity conditions: 68°-77° F (20° - 25° C) and 50±5% R. H.
- Typical Adhesion Values: **180° Peels**

Substrate	24 hrs	1 week
Stainless Steel	4.4 lbs/in	5.1 lbs/in
Glass	4.7 lbs/in	5.3 lbs/in

NOTE: Tested per ASTM D 1000. Always pre-test your specific substrate prior to actual application.

- Reflectivity: NA
- Typical Gloss\*: 70 at 60°

Avery Graphics™ A5 Opaque page 1 of 2  
AnswerLine: 800-443-9380  
Signage.averygraphics.com